



Class 1

Building Product Information Requirement

Product Name:

Fregio Blu Maiolica 60 X 240

Product Identifier:

FREGIOBLU

Product Description & Specifications:

REGIO is a decorative wall tile collection that captures the charm of the Mediterranean-style Majolica pottery on subway or brick shaped tiles. Characterised by an ornate designs that capture the wear and tear of time, with the shiny decorative surfaces appearing to have been eroded and erased. Where the white base tile emerges, faux chipping appears to reveal the colour of the red clay beneath.

Transform any space—be it your bedroom, bathroom, kitchen, laundry, or bar—with the exquisite and unique design of the Fregio Collection. Perfect for both residential and commercial settings, these tiles turn interior walls into artistic masterpieces.

Available in three stunning decorative colourways in Blu, Verde and Black, plus a sleek non-decorative White option - Fregio Bianco Natural.

Key features:

- Wall only
- 60x240mm
- Three colours in the decorative Maiolica - Green, Blue and Black
- One solid colour – Bianco Naturale – that runs through all the tiles
- Multiple faces randomly supplied
- Made in Italy
- Glazed Porcelain

Finish:	MATT
Material:	PORCELAIN
Origin:	ITALY
Size:	60 x 240
Variation:	3
Weight:	18 kg per m ²
Rectified:	Yes
Sealing Required:	No
Colour:	Blue
m² Per Box:	0.6912
Tiles Per Pack:	48

Image:



Manufacturer:

Tile Depot Approved supplier. All our manufacturers produce material to comply with the technical requirements and tolerances prescribed by ISO13006.

Legal and Trading name of the importer:



Tile Depot LP

NZBN: 9429049866773

Address: 83 Harris Rd, East Tamaki, Auckland, New Zealand

Website: www.tiledepot.co.nz

Email: info@tiledepot.co.nz

Phone: 0800 845 3337



Relevant Building Code Clauses:

D1 – Access Routes Refer Section 2.0

Requires access routes to have an adequate slip resistance surface. For housing this requirement applies only to the access route on the approach to the main entrance and not inside that entrance and not on the approach to other entrances. The internal access routes of housing, including kitchens and bathrooms shall be assumed to be dry in normal use. When specifying suitability of a selected tile refer to D1 2.0 in conjunction with the slip rating of the material provided.

E3 – Internal Moisture

Clause 3.1.1 references product porosity. Ceramics are a commonly accepted industry solution and porcelain tiles have a very low water absorption level (less than 0.5%). Higher porosity ceramic and natural stone products can be presented as an alternative solution. Ceramic wall tiles have an impervious glaze and a protective layer called an engobe. Natural stone can be sealed with a penetrating sealer. Grouts can be sealed or the use of epoxy grouts will minimise water penetration to the substrate. If in doubt check with the specifier prior to installation.

C3 – Protection from Fire

The Building code relating to fire rating regulations and standards requires specifiers to provide documentation such as fire certificates for materials used in construction. Ceramics are in itself fire-resistant material, most being manufacturer in excess of 1200 degree Celsius. Testing and providing such certification is therefore not relevant to the ceramics industry.

Ceramics are non-combustible and they do not release fumes or toxic gases in the event of a fire. Ceramics contain no sealants, waxes or other chemicals that could release VOC's into the environment. Ceramics do not pose a risk of spreading or intensifying a fire.



Statement on how this product is expected to contribute to compliance:

D1 – Access Routes – subject to intended use, location and slip resistance properties of selected tile.
C3 – Protection from Fire - Ceramics do not pose a risk of spreading or intensifying a fire.

Limitations on the use of this building product:

Porcelain and ceramic tiles will not perform without a suitable substrate. It is the responsibility of the specification designer and / or installer to ensure an adequate substrate prior to installation.

Refer to the individual product specifications which outline characteristics including material, surface finish, size, PEI, weight and slip rating where applicable.

Installation Requirements:

Tiles must be installed by a competent trades person. Relevant resources include:

- MBIE Guide to tolerances
- Branz Good Practice guide – Tiling
- NCTC – Tile & Tiling Guide
- BCITO training and accreditation
- Installation systems from reliable adhesive & waterproofing manufacturers

Tiles are one of the most hygienic and easily maintained wall and floor surfaces available. A simple routine clean is required regularly with suitable tile specific cleaning agents.

This product is not subject to a warning or ban under section 26 of the Building Act 2004

Version 1

Date: November 22 2024