



## Class 1

Building Product Information Requirement

Product Name:

Statuario White Super Gloss 300 X 600

Product Identifier:

STATUARIO30

Product Description & Specifications:

Statuario is considered to be the most precious of all the Italian marbles with a white base and distinctive veining that can range in colour from gold to grey. Statuario White Super Gloss is a polished porcelain replica of this stunning stone. It has 9 different tile faces, replicating the variation found in the natural marble and a glossy polished surface enhancing its high-end appeal. Also available in a 600x600mm format and a satin finish. Statuario White Super Gloss can be used throughout residential interiors and on both floors and walls.

|                               |                            |
|-------------------------------|----------------------------|
| <b>Finish:</b>                | POLISHED                   |
| <b>Material:</b>              | PORCELAIN                  |
| <b>Origin:</b>                | CHINA                      |
| <b>Size:</b>                  | 300 x 600                  |
| <b>PEI:</b>                   | 4                          |
| <b>Variation:</b>             | 3                          |
| <b>Weight:</b>                | 20.1 kg per m <sup>2</sup> |
| <b>Rectified:</b>             | Yes                        |
| <b>Sealing Required:</b>      | No                         |
| <b>Colour:</b>                | White                      |
| <b>m<sup>2</sup> Per Box:</b> | 1.44                       |
| <b>Tiles Per Pack:</b>        | 8                          |

Image:



Manufacturer:

Tile Depot Approved supplier. All our manufacturers produce material to comply with the technical requirements and tolerances prescribed by ISO13006.

Legal and Trading name of the importer:

**Tile Depot LP**  
NZBN: 9429049866773  
Address: 83 Harris Rd, East Tamaki, Auckland, New Zealand  
Website: [www.tiledepot.co.nz](http://www.tiledepot.co.nz)  
Email: [info@tiledepot.co.nz](mailto:info@tiledepot.co.nz)  
Phone: 0800 845 3337



## Relevant Building Code Clauses:

### **D1 – Access Routes** Refer Section 2.0

Requires access routes to have an adequate slip resistance surface. For housing this requirement applies only to the access route on the approach to the main entrance and not inside that entrance and not on the approach to other entrances. The internal access routes of housing, including kitchens and bathrooms shall be assumed to be dry in normal use. When specifying suitability of a selected tile refer to D1 2.0 in conjunction with the slip rating of the material provided.

### **E3 – Internal Moisture**

Clause 3.1.1 references product porosity. Ceramics are a commonly accepted industry solution and porcelain tiles have a very low water absorption level (less than 0.5%). Higher porosity ceramic and natural stone products can be presented as an alternative solution. Ceramic wall tiles have an impervious glaze and a protective layer called an engobe. Natural stone can be sealed with a penetrating sealer. Grouts can be sealed or the use of epoxy grouts will minimise water penetration to the substrate. If in doubt check with the specifier prior to installation.

### **C3 – Protection from Fire**

The Building code relating to fire rating regulations and standards requires specifiers to provide documentation such as fire certificates for materials used in construction. Ceramics are in itself fire-resistant material, most being manufacturer in excess of 1200 degree Celsius. Testing and providing such certification is therefore not relevant to the ceramics industry.

Ceramics are non-combustible and they do not release fumes or toxic gases in the event of a fire. Ceramics contain no sealants, waxes or other chemicals that could release VOC's into the environment. Ceramics do not pose a risk of spreading or intensifying a fire.



Statement on how this product is expected to contribute to compliance:

D1 – Access Routes – subject to intended use, location and slip resistance properties of selected tile.  
C3 – Protection from Fire - Ceramics do not pose a risk of spreading or intensifying a fire.

Limitations on the use of this building product:

Porcelain and ceramic tiles will not perform without a suitable substrate. It is the responsibility of the specification designer and / or installer to ensure an adequate substrate prior to installation.

Refer to the individual product specifications which outline characteristics including material, surface finish, size, PEI, weight and slip rating where applicable.

Installation Requirements:

Tiles must be installed by a competent trades person. Relevant resources include:

- MBIE Guide to tolerances
- Branz Good Practice guide – Tiling
- NCTC – Tile & Tiling Guide
- BCITO training and accreditation
- Installation systems from reliable adhesive & waterproofing manufacturers

Tiles are one of the most hygienic and easily maintained wall and floor surfaces available. A simple routine clean is required regularly with suitable tile specific cleaning agents.

This product is not subject to a warning or ban under section 26 of the Building Act 2004

Version 1

Date: November 22 2024